TL-50

AWS A5.1 E7016 EN ISO 2560-A-E 42 3 B 1 2 JIS Z 3211 E4916

Characteristics and Applications:

TL-50 is a low hydrogen type electrode for the welding of 490N/mm² high tensile steel. The welding can be done with stable arc, less spatters, good slag covering, release, and good X-ray soundness. It is suitable for low alloy steels, medium carbon steels, heavy steel plates, cast steels. Proper base metals such as: structural steel, steel tubes for Heat transfer, plate for pressure vessel, low-alloy steel tube, mechanical structural carbon-steel plate, API-5L.A25.X52.X56.X60.X65, etc. Due to good X-ray and mechanical properties, TL-50 is used for skill testing and competition by choice.

Notes on usage:

- 1. Clean up the contaminations on the base metal to avoid porosity and crack.
- 2. Dry the electrodes at 300-350 for 60 minutes, and keep at 100-150 before using.
- 3. Use back-step method to prevent arc starting from blowholes and hold for 3-5 seconds at every end-up.
- 4. Maintain short arc length. Moving range should be controlled within 3 times of the wire's dia when you are welding with weave method.
- 5. Do not exceed the range of recommended current. Over heat input might decrease the impact value.

Typical chet eed typic3ds 14.318 0 Td (150)Tj EMC /Sp-0 01(3ds 14.o)1ow 5.1548

