

## Characteristics and Applications:

TLH-581 is an iron-powder low hydrogen type electrode for all-position welding of 490N/mm<sup>2</sup> grade high tensile steel. It is designed for single and multiple pass applications. The product has good welder appeal and produces a stable arc with low spatter generation. TLH-581 produces weld metals with excellent mechanical properties and impact toughness at low temperature (-45 W) and low diffusible hydrogen. Its features make the product suitable for low alloy steels, medium carbon steels, heavy steel plates, cast steels, aluminum killed steel of LPG and especially for welding of steels with poor weldability.


## Notes on usage:

1. Be sure to clean up the contaminations on the base metal.
2. Unless the storage condition is secured and the packing is not damaged, we highly recommend to dry the electrodes at 350-400 W for 1-2 hours before using.
3. Take the back-step method to prevent blowholes at the arc starting.
4. Maintaining short arc length is highly recommended to prevent moisture pick-up.

## Typical chemical composition of weld metal (wt%) :

C	Mn	Si	P	S
0.065	1.40	0.60	0.02	0.007

## Typical mechanical properties of weld metal ::



The information contained or otherwise referenced herein is presented only as typical, without guarantee or warranty, and the actual results may produce different results. The information is not intended to be used as a recommendation for any welding application or technique and should not be used as a substitute for any applicable code or standard.