

FabStar 721

AWS A5.26 EG72T-1

Characteristics and Applications:

FabStar 721 is a self-shielded flux-cored wire used for single pass, vertical up, electrogas welding of shipbuilding, heavy equipment fabrication and structural welding and storage tank. It is suitable for welding of mild steel and high tensile steels with high deposition rate and with or without consumable guide.

Notes on usage:

1. Use DC(+) polarity.
2. Composition of consumable guide tube should be as close as possible to parent steel and be aware to add an insulating ring to the tube made without insulating coating to prevent from a short circuit.
3. Mechanical properties depend on plate chemistry and joint geometry.
4. Pre-heat the workpiece and start-up zone.
5. Baffle plate should be tightened firmly to prevent a leak of deposited metal.
6. Control all parameters with care during welding, such as shape of weld joint, tube material, cooling rate.
7. Keep the product dry, while it is stored or delivered.

Typical chemical composition of weld metal (wt%) :

C	Mn	Si	P	S	Mo
0.05	1.50	0.35	0.015	0.007	0.18

Typical mechanical properties of weld metal on A36 base metal :

Yield strength MPa(ksi)	Tensile strength MPa(ksi)	Elongation %	Charpy V-Notch J (ft-lbf) -30°C(-20 °F)
441(64)	540(78)	25	50(37)

Sizes and recommended current range (DC +polarity):

Diameter (mm)	1.6		2.4		3.0			
Parameters	9	12	12	19	19	25	38	50
Thickness	280	300	350	400	510	580	750	890
Wire Feed Speed (cm/min)	30	32	36	38	35-38	38-40	42-44	42-44
Voltage(Volt)								

Information contained or otherwise referenced herein is presented only as "typical" without guarantee or warranty and Tien Tai Electrode Co., Ltd. expressly disclaims any liability created from any reliance thereon. Typical data is obtained when welded and tested in accordance with AWS specification. Other tests and procedures may produce different results. No data is to be construed as recommendation for any welding condition or technique not controlled by Tien Tai Electrode Co., Ltd.