

Characteristics and Applications:

TWE-711Ni is a gas-shielded flux cored wire designed for mild steel and 490N/mm² high tensile steel. It is suitable for all position welding. It provides stable arc, less spatter, easy slag removable, and excellent X-Ray inspection. It provides good low-temperature impact value due to 0.4%Ni in weld metal. The typical applications include shipbuilding, vessels, piping etc.

Notes on usage:

1. Use (DC+) polarity.
2. Use CO₂ as shielding gas.
3. To get desired impact value, you must control welding heat input, as excessive heat input would decrease notch toughness.
4. Keep the product dry, while it is stored or delivered.

Typical chemical composition of weld metal (wt%):

C	Mn
---	----

TienTai Electrode Co., Ltd. expressly disclaims any liability for the information contained herein. Other tests and procedures may produce different results. TienTai Electrode Co., Ltd.

* The information contained or otherwise referenced herein is presented only as "typical" without guarantee or warranty. No data is to be construed as recommendation for any welding condition or technique not controlled by TienTai Electrode Co., Ltd.

TienTai Electrode Co., Ltd.
No. 100, Sec. 2, Zhongxing Rd., Taichung City 404, Taiwan
E-mail: ttw@ttweld.com
Tel: +886-4-2222-0000

