

# TWE-811Ni1

AWS A5.29 E81T1-Ni1C  
EN ISO 17632-A-T 46 3 1Ni P C1 1 H10

## Characteristics and Applications:

TWE-811Ni1 is a titania type flux-cored wire with CO<sub>2</sub> shielding gas for all-position welding. It is designed for welding 590 N/mm<sup>2</sup> high tensile steel used in low temperatures.

It provides good weldability with smooth bead appearance, less spatter and stable arc as well as good impact properties down to -30 °C.

It is also suitable for welding on construction machinery, shipbuilding, offshore, structures, bridges, storage tanks and piping.

## Notes on usage:

1. Excessive heat input should reduce impact value. Therefore, perform welding with selecting proper heat input based on the required impact value.
2. Must preheat at 50~150 °C depending on steels, plate thickness and restraint.
3. Use DC(+) polarity.
4. Use 99.8% or higher purity of CO<sub>2</sub> Gas.
5. Keep the product dry, while it is stored or delivered.


## Typical chemical composition of weld metal (wt%):

C	Mn	Si	P	S	Ni
0.04	1.20	0.25	0.015	0.009	1.00

## Typical mechanical properties of weld metal:

Yield strength MPa(ksi)	Tensile strength MPa(ksi)	Elongation %	Charpy V-Notch J(ft-lbf)		PWHT
			-30 (-20 )	110(81)	
602(87)	650(94)	26	-40 (-40 )	95(70)	--
522(76)	590(86)	30	-40 (-40 )	92(68)	590 *8hr

## Welding position:



## Sizes and recommended parameter range (DC + ) : Stick out:15-25(mm), flow rate:20-25(l/min):

Position	Diameter (mm)	1.2	1.4	1.6
	F HF		180A-300A / 24V-36V	180A-350A / 24V-36V
VU OH		150A-220A / 22V-28V	150A-220A / 22V-28V	160A-220A / 22V-28V
H		150A-260A / 22V-31V	160A-280A / 22V-30V	180A-280A / 23V-32V

\* The information contained or otherwise referenced herein is presented only as "typical" values.

without guarantee or warranty of Tien Tai Electrode Co., Ltd. excepted disclaims any liability.

may produce different results.

No data is to be construed as recommendation for any work.

condition or technical specifications not controlled by Tien Tai Electrode Co., Ltd.